

## Krontec Quicklift AirJack - Safety Valve

Brand: **Krontec**

Product Code: **LL-24**



### Krontec Quicklift AirJack - Safety Valve

LL-24 Krontec High Performance "Springless Retract" Motorsport Air Jack Includes an integrated safety blow off valve to protect the unit from incorrect use or abuse by overpressure.

Should for any reason and overpressure be introduced to the jack, either by damaged equipment or equipment failure or even incorrect handling, a safety overpressure valve (internal) activates to relieve the pressure and protect the unit and personnel. A factory set activation pressure of 55 Bar is provided.

Operating Pressure/Lift Capacity: 40 Bar(Maximum)= 750kg, 30 Bar= 562kg, 20 Bar=375kg.

This jack is used in the FRONT of the Lamborghini Huracan ST (Super Trofeo)

This racing jack incorporates the latest in technological advancements and features a unique internal safety blow off valve to protect the jack from over pressurisation. It is features such as this, and many other quality attributes that ensures you get the best product available on the market today.

If you are building a race vehicle and are looking for the best products at competitive prices - look no further, we have what you need! We are also able to manufacture many specific items for your car build, all to a traceable certified standard. Krontec is a quality certified design and manufacturing company to the highest of standards including ISO 9001:2008 & EN 9100:2003.

#### Specifications

Lifting Capacity	40 Bar(Maximum)= 750kg 30 Bar= 562kg 20 Bar=375kg
Mounting Diameter	64mm
Outside Diameter	60mm
Stroke	230mm
Thread Size	M60x1.5
Weight	974 grams (without nut)

As with all of the Krontec products we supply, this jack is fully supported by us.

### **Attachments**

[Krontec Air Jack Safety & Instruction Manual](#)

[Krontec LL-24 Jack Dimensions](#)